

ACOUSTIC PRODUCTS

DEWETON ACOUSTIC PANELS

K13/170 NBS STYLE TECHNICAL SPECIFICATION

ACOUSTIC PANELS TO: _____

Refer to drawings: _____

Manufacturer and reference: **Deweton** acoustic panels, design reference by
Acoustic Products Ltd
139 Tankerton Road
Whitstable
Kent
CT5 2AW
Tel 01227 281140
Fax 01227 281141
Email enquiries@acoustic-products.co.uk

Panel Substrate: 25 mm thick DIN B2 non fire rated extruded tubular chipboard/25 mm thick
DIN B1 fire retardant extruded tubular chipboard

Front Surface Finish:veneer with DIN B2 non fire rated factory
applied lacquer finish/DIN B1 fire retardant factory applied
lacquer finish

Factory spray painted to RAL/NCS colour reference

Melamine colour/design reference

Laminate colour/design reference

Edges: Square cut raw MDF/Square cut "Sasmox"/Veneered to match/Factory
spray painted to match/Melamine to match/Laminate to match.

Panel sizes & quantities: (panel sizes 1820 mm x 604 mm/2600 mm
x 604 mm/3200 mm x 604 mm, even number quantities of each panel size required, cut to specific
sizes in the factory subject to waste surcharge).

Acoustic Insulation: 30 mm thick mineral wool (40-60 kgs/cu M, 2.5-3.75 pcf) behind panels

Installation: Method of fixing panels & support framework: in accordance with
manufacturer's recommendations