

# Eurofix

A Comprehensive range of  
modular Data and Media units



View range online

EuroFix Modules are designed to fit most Hamilton Plate Ranges.

- Standard Euro apertures
- Plates affix to BS wall boxes
- Inserts clip into plates
- EuroFix White Polycarbonate Plates
- USB Charger/Power Socket Module
- AV/Audio/HDMI Outlet Modules
- Digital Television/Satellite Outlet Modules
- Data Outlet Modules
- Hotel Card Switch with LED Modules

Concealed fixings to give screwless aesthetic

Superb finishes, including four shades of bronze



Elegant finishes with complementary finishes on switch inserts



Comprehensive range of electrical accessories



Grid Fix and Eurofix options also available (see separate GRID-IT and EuroFix sections)

# EuroFix




## Power Sockets

EURO RANGE



50x50mm Module 13A UK Unswitched Socket		
	Black	MOD-ENG13A B
	White	MOD-ENG13A W
Module Size: 50 x 50mm Wall Box Depth: 35mm		



13A Universal Unswitched Socket 50x50mm Module		
	Black	MOD-UNIV B
	White	MOD-UNIV W
Module Size: 50 x 50mm Wall Box Depth: 47mm		

**NEW**

USBAX2 Charger 50x50mm Module Ultrafast charging power delivery + Quick Charge		
	Black	MOD-USBA+C45W-PDB
	White	MOD-USBA+C45W-PDW
	Quartz Grey	MOD-USBA+C45W-PDQG
Module Size: 50 x 50mm Wall Box Depth: 35mm		

## International Power Sockets

50x50mm Module 16A German Unswitched Socket		
	Black	MOD-GER16A B
	White	MOD-GER16A W
	Quartz Grey	MOD-GER16A QG
Module Size: 50 x 50 mm Wall Box Depth: 47mm		




50x50mm Module 15A 110V American Unswitched Socket		
	Black	MOD-USA15A B
	White	MOD-USA15A W
	Quartz Grey	MOD-USA15A QG
Module Size: 50 x 50mm Wall Box Depth: 35mm		

# EuroFix

## Television Coaxial Sockets

EURO RANGE



25x50mm Module  
Non-Isolated  
TV 1in/1out

	Black	MOD-TV B
	White	MOD-TV W
	Quartz Grey	MOD-TV QG

**Technical Information:** Non Isolated Co-Ax outlet (IEC 169 Female Socket)

Module Size: 25 x 50mm  
Wall Box Depth: 35mm



25x50mm Module  
Isolated  
TV 1in/1out

	Black	MOD-TVIB
	White	MOD-TVIW

**Technical Information:** Isolated Co-Ax outlet (IEC 169 Female Socket)

Module Size: 25 x 50mm  
Wall Box Depth: 35mm




50x50mm Module  
Isolated  
TVFM Diplexer 1in/2out

	Black	MOD-TVFM B
	White	MOD-TVFM W

**Technical Information:** Isolated Diplexer Co-Ax outlets for use with combined TV and FM signal

Module Size: 50 x 50mm  
Wall Box Depth: 35mm




25x50mm Module  
Non-Isolated  
Satellite

	Black	MOD-SATN B
	White	MOD-SATN W
	Quartz Grey	MOD-SATN QG

**Technical Information:** Non Isolated F-Type outlet for Satellite or Cable TV installations

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module  
Isolated  
Satellite

	Black	MOD-SATI B
	White	MOD-SATI W
	Quartz Grey	MOD-SATI QG

**Technical Information:** Isolated F-Type outlet for Satellite or Cable TV installations where a DC signal back to the LNB unit on the Satellite Dish is NOT required

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

## Cable Tidy

Cable Tidy  
50x50mm Module

	Black	MOD-50TIDY B
	White	MOD-50TIDY W
Module Size: 50 x 50mm Wall Box Depth: 35mm		

# EuroFix

## Digital Television Sockets - Fully Screened Non Isolated / DAB Compatible

EURO RANGE

50x50mm Module  
Non-Isolated  
TV+FM+SAT Triplexer  
1in/3out  
(DAB Compatible)

	Black	MOD-DTRID B
	White	MOD-DTRID W
	Quartz Grey	MOD-DTRID QG

**Technical Information:** Triplexer for use with combined TV, FM and Satellite Signals, (DAB compatible)  
**Frequency:** TV = 5-68 MHz, 125-860 MHz, FM = 88-108 MHz, SAT DC = 950-2200 MHz

Module Size:	50 x 50mm
Wall Box Depth:	35mm

50x50mm Module  
Non-Isolated  
TV+FM+SAT1+SAT2 Quadplexer  
2in/4out  
(DAB Compatible)

	Black	MOD-DENT B
	White	MOD-DENT W
	Quartz Grey	MOD-DENT QG

**Technical Information:** Quadplexer for use with combined TV, FM and Satellite Signals, (DAB compatible)  
**Frequency:** TV = 5-68 MHz, 125-860 MHz, FM = 88-108 MHz, SAT DC = 950-2200 MHz

Module Size:	50 x 50mm
Wall Box Depth:	35mm

25x50mm Module  
Non-Isolated  
TV (female)

	Black	MOD-DTVF B
	White	MOD-DTVF W
	Quartz Grey	MOD-DTVF QG

**Technical Information:** TV outlet (IEC 169 Female Socket). Usually used for FM (DAB) outlet.  
**Frequency:** TV DC = 5-2200 MHz

Module Size:	25 x 50mm
Wall Box Depth:	35mm

25x50mm Module  
Non-Isolated  
TV (Male)

	Black	MOD-DTVM B
	White	MOD-DTVM W
	Quartz Grey	MOD-DTVM QG

**Technical Information:** TV outlet (IEC Male Socket). Usually used for FM (DAB) outlet.  
**Frequency:** FM DC = 5-2200 MHz

Module Size:	25 x 50mm
Wall Box Depth:	35mm

25x50mm Module  
Non-Isolated  
Satellite

	Black	MOD-DSAT B
	White	MOD-DSAT W

**Technical Information:** F Type Satellite Outlet.  
**Frequency:** SAT DC = 50-2200 MHz

Module Size:	25 x 50mm
Wall Box Depth:	35mm



25x50mm Module Latching Audio Connector 3 Pin XLR Socket		
	Black	MOD-XLR B
	White	MOD-XLR W

Technical Information: Current Rating: 15A at 120VAC Contact Resistance 5mW Max.

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module 3.5mm Stereo Socket (MP3) Screened		
	Black	MOD-MP3 B
	White	MOD-MP3 W

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module D-Range PC Socket 9 Pin		
	Black	MOD-DIN9 B
	White	MOD-DIN9 W

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module D-Range SVGA Socket 15 Pin		
	Black	MOD-SVGA B
	White	MOD-SVGA W

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module 1 x Gold Phone/Audio Socket (1xBlack)		
	Black	MOD-RCA1 B
	White	MOD-RCA1 W

Technical Information:  
Current Rating: Mating Connector Dependent  
Contact Resistance: Mating Connector Dependent  
Insulation Resistance: >1GW  
Dielectric Strength: 500V DC  
Life Cycle: 5000 Cable OD: 4-9mm  
Solder Compatibility: IEC 68-2-20  
Operating Temperature: -25°C to +70°C

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module 2 x Gold Phone/Audio Socket (1xRed 1xBlack)		
	Black	MOD-RCA2 B
	White	MOD-RCA2 W



Technical Information:  
Current Rating: Mating Connector Dependent  
Contact Resistance: Mating Connector Dependent  
Insulation Resistance: >1GW  
Dielectric Strength: 500V DC  
Life Cycle: 5000 Cable OD: 4-9mm  
Solder Compatibility: IEC 68-2-20  
Operating Temperature: -25°C to +70°C

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module 3 x Gold Composite Video/Audio Socket (1XRed 1xWhite 1xYellow)		
	Black	MOD-RCA3 B
	White	MOD-RCA3 W

Technical Information:  
Current Rating: Mating Connector Dependent  
Contact Resistance: Mating Connector Dependent  
Insulation Resistance: >1GW  
Dielectric Strength: 500V DC  
Life Cycle: 5000 Cable OD: 4-9mm  
Solder Compatibility: IEC 68-2-20  
Operating Temperature: -25°C to +70°C



Module Size: 25 x 50mm  
Wall Box Depth: 35mm



25x50mm Module 2 x Gold Binding Post Socket (1xRed 1xBlack)		
	Black	MOD-BAN2 B
	White	MOD-BAN2 W

Technical Information:  
Socket: 4mm  
Suitable for 'Banana' Plugs

Module Size: 25 x 50mm  
Wall Box Depth: 35mm

25x50mm Module HDMI Chassis Mounted Socket Type A (Female Mounted-Female Free)		
	Black	MOD-HDMI B
	White	MOD-HDMI W
Cable Length:	155mm	
Module Size:	25 x 50mm	
Wall Box Depth:	35mm	

25x50mm Module USB 2 Panel Mounted Socket Type A (Female Mounted - Male Free)		
	Black	MOD-USBAFM B
	White	MOD-USBAFM W
Cable Length:	500mm	
Module Size:	25 x 50mm	
Wall Box Depth:	35mm	

25x50mm Module USB 2 Panel Mounted Socket Type A (Female Mounted -Female Free)		
	Black	MOD-USBAFF B
	White	MOD-USBAFF W
Cable Length:	155mm	
Module Size:	25 x 50mm	
Wall Box Depth:	35mm	

## Telephone and Data Outlets

EURO RANGE

25x50mm Module Telephone Master			25x50mm Module Telephone Slave			25x50mm Module RJ12 Outlet - Unshielded			Carrier for Keystone RJ Data Socket 25x50mm Module		
	Black	MOD-TCM B		Black	MOD-TCS B		Black	MOD-J12 B		Black	MOD-KSC B
	White	MOD-TCM W		White	MOD-TCS W		White	MOD-J12 W		White	MOD-KSC W
	Quartz Grey	MOD-TCM QG		Quartz Grey	MOD-TCS QG						
<b>Technical Information:</b> Used as the first socket outlet on the installation			<b>Technical Information:</b> Used as the extension socket outlets of the installation			<b>Technical Information:</b> Can be used as either an RJ11 (4 wires) or RJ12 (6 wires)					
<b>Module Size:</b> 25 x 50mm			<b>Module Size:</b> 25 x 50mm			<b>Module Size:</b> 25 x 50mm			<b>Module Size:</b> 25mm x 50mm		
<b>Wall Box Depth:</b> 25mm			<b>Wall Box Depth:</b> 25mm			<b>Wall Box Depth:</b> 35mm			<b>Wall Box Depth:</b> 35mm		
25x50mm Module RJ45 CAT 6S Outlet - Shielded			25x50mm Module RJ45 CAT 5E Outlet - Unshielded			25x50mm Module RJ45 CAT 6 Outlet - Unshielded			25x50mm Module RJ45 Angled - Unshielded		
	Black	MOD-J45-C6S B		Black	MOD-J45-C5 B		Black	MOD-J45-C6 B		45 Degree Angle Cat 5 Module	MODA-J45-C5B
	White	MOD-J45-C6S W		White	MOD-J45-C5 W		White	MOD-J45-C6 W		45 Degree Angle Module	MODA-J45-C5W
				Quartz Grey	MOD-J45-C5 QG		Quartz Grey	MOD-J45-C6 QG		Modular 50/25mm Socket RJ-45-Front Black 45 Deg	MODA-J45-C6B
<b>Technical Information:</b> Can be used in both EIA 568A and EIA 568B wiring schedules			<b>Technical Information:</b> Enhanced CAT 5E performance (Unshielded) Can be used in both EIA 568A and EIA 568B wiring schedules			<b>Technical Information:</b> Can be used in both EIA 568A and EIA 568B wiring schedules					
<b>Module Size:</b> 25mm x 50mm			<b>Module Size:</b> 25 x 50mm			<b>Module Size:</b> 25 x 50mm			<b>Module Size:</b> 50/25mm Socket RJ-45-Front White 45 Deg		
<b>Wall Box Depth:</b> 47mm			<b>Wall Box Depth:</b> 47mm			<b>Wall Box Depth:</b> 47mm			<b>Wall Box Depth:</b> 47mm		

## Blanking Insert Plates

12.5x50mm Half Module Blank			25x50mm 1 Module Blank		
	Black	MOD-HALFBLANK B		Black	MOD-1BLANK B
	White	MOD-HALFBLANK W		White	MOD-1BLANK W
	Quartz Grey	MOD-HALFBLANK QG		Quartz Grey	MOD-1BLANK QG
<b>Module Size:</b> 12.5 x 50mm			<b>Module Size:</b> 25 x 50mm		

## EuroFix Apertured Plates

50x50mm 2 Module Aperture  
 Designed to hold one 50 x 50mm module or  
 two 25 x 50mm modules or  
 one 25 x 50mm module and  
 two 12.5mm x 50mm Blanking Plates



White	<b>MOD-P2MW</b>
<b>Nominal Plate Size:</b>	86 x 86mm
<b>Aperture:</b>	50 x 50mm

50x100mm 4 Module Aperture  
 Designed to hold one 100 x 50mm module or  
 two 50 x 50mm modules or  
 one 50 x 50mm module and two 25 x 50mm or  
 four 25 x 50mm modules



White	<b>MOD-P4MW</b>
<b>Nominal Plate Size:</b>	146 x 86mm
<b>Aperture:</b>	100 x 50mm

## Hotel Card Switch with LED



MOD-C11-BC-W



1 gang 10A (6AX) Card  
 Switch On/Off with Blue  
 LED Locator

Insert Finish / Surround Colour	
Antique Brass/Black	<b>MOD-C11-AB-B</b>
Black Nickel/Black	<b>MOD-C11-BK-B</b>
Bright Chrome/White	<b>MOD-C11-BC-W</b>
Bright Chrome/Black	<b>MOD-C11-BC-B</b>
Polished Brass/White	<b>MOD-C11-PB-W</b>
Polished Brass/Black	<b>MOD-C11-PB-B</b>
Satin Chrome/White	<b>MOD-C11-SC-W</b>
Satin Chrome/Black	<b>MOD-C11-SC-B</b>
Satin Brass/White	<b>MOD-C11-SB-W</b>
Satin Brass/Black	<b>MOD-C11-SB-B</b>
Satin Stainless/White	<b>MOD-C11-SS-W</b>
Satin Stainless/Black	<b>MOD-C11-SS-B</b>
Black Plastic/Black	<b>MOD-C11-BL-B</b>
White Plastic/White	<b>MOD-C11-WH-W</b>
<b>Nominal Size:</b>	50 x 50mm
<b>Minimum Wall Box Depth:</b>	35mm