

DESCRIPTION

Johnstone's Trade Quick Drying Metal Primer is a water based, anticorrosive metal primer. With outstanding adhesion, it is ideal use over ferrous and non-ferrous metals, including galvanised metal and can be easily overcoated with Johnstone's Trade Quick Drying Steel & Cladding Topcoat.

RECOMMENDED USES



Primes suitably prepared ferrous metals, such as, steel, iron and prepared galvanised steel.

SPECIAL PROPERTIES

Excellent anti-corrosive properties and adhesion to metal. Quick drying and low odour.

COLOUR RANGE

White.

FINISH

Matt.

VOLUME SOLID

32%.

COVERAGE



Johnstone's Trade Quick Drying Metal Primer will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 34µm.

DRYING TIME



Under normal conditions, touch dry in 1-2 hours and recoatable after 4 hours. Ensure good ventilation during application and drying.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/i): 140g/l (2010) This product contains max 100 g/l VOC



KEY PROPERTIES

- Specially formulated for metal
- Anti-corrosive
- Excellent adhesion properties

PREPARATION

All surfaces to be painted should be clean, dry and free from grease and loose and flaking material. Any existing rust or millscale should be removed. Lightly sand the surface with a fine waterproof abrasive paper and wipe clean. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well before use. Easy to apply by brush or roller. Also suitable for application by airless spray. A second coat serves as an excellent undercoat. Do not apply in temperatures below 8°C or in damp conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre.