

## DESCRIPTION

Johnstone's Trade Semi-Gloss Topcoat is specially formulated to provide long lasting protection against corrosion on metal substrates, cladding and plastisol. It provides excellent UV resistance for all round weather protection. Use with Johnstone's Trade Quick Dry Zinc Phosphate Primer for added protection against corrosion.

## RECOMMENDED USES



Plastisol cladding, suitably prepared steel and other metallic surfaces.

## SPECIAL PROPERTIES

UV resistance and good weather resistance for all round weather protection.

## COLOUR RANGE

Available in a range of colours via our Tinting System.

## FINISH

Semi-gloss.

## VOLUME SOLID

50%.

## COVERAGE



Johnstone's Trade Semi-Gloss Topcoat will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 100µm, dry: 50µm.

## DRYING TIME



Recoat after 16-24 hours under normal conditions.

## TRANSPORTATION & STORAGE

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position. STORE AWAY FROM HEAT AND FLAME.

## THINNER

Cleaner: White Spirit.

## VOC CONTENT

EU limit value for this product (Cat A/i): 500 g/l (2010). This product contains max 450g/l VOC.



## KEY PROPERTIES

- Specially formulated for metal
- UV & water resistant

## PREPARATION

**STEEL:** Prepare surface and prime accordingly. If overcoating an existing paint ensure the surface is clean and dry.

**CLADDING:** Clean thoroughly with Johnstone's Trade Cleaner & Degreaser after removing all loose and flaking paint, salts etc. Wash down with clean water. All bare areas of steel/aluminium must be suitably prepared and spot primed with Johnstone's Trade Quick Dry Zinc Phosphate Primer unless specified as part of a written Johnstone's Trade Technical Specification. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir thoroughly before use. Suitable for application by brush or roller.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

5 Litre