

DESCRIPTION

Johnstone's Trade Aluminium Paint is a solvent borne, protective metallic finish formulated for use on suitably prepared metal surfaces such as storage tanks, ducting and pipework. Based on an oil varnish medium and aluminium flake it will withstand temperatures up to 150°C. Its brilliant lustre has the added benefit of reflecting solar radiation.

RECOMMENDED USES



Exterior of storage tanks, ducting and pipework. Avoid areas that are consistently handled to prevent the transfer of aluminium.

SPECIAL PROPERTIES

Heat resistant up to 150°C. Solar reflective properties.

COLOUR RANGE

Silver.

FINISH

Metallic.

VOLUME SOLID

48%

COVERAGE



Johnstone's Trade Aluminium Paint will cover approximately 14-16 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 66µm, dry: 32µm.

DRYING TIME



Recoat after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/I): 500g/l (2010). This product contains max 500g/l VOC.



KEY PROPERTIES

- For use on storage tanks, ducting and pipework
- Heat resistant up to 150°C
- Solar reflective

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Any rust should be removed by wire brushing. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime bare surfaces with the appropriate Johnstone's Trade Specialist Primer. Special precautions should be taken during surface preparation of pre- 1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre and 5 Litre.