

## DESCRIPTION

Johnstone's Trade Jonmat is a high quality yet economical premium contract matt emulsion. It provides excellent coverage and has outstanding dry & wet opacity on interior walls and ceilings leaving a permeable breathable finish. Ideal for use on new plaster or plasterboard.

## RECOMMENDED USES

**INTERIOR** Suitable for interior use.



## TYPE OF SUBSTRATE

New plaster. Also suitable for use on aged plaster, wall boards, concrete, cement rendering, brickwork and blockwork in internal situations.

## COLOUR RANGE

Over 7,000 colours are available via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

23%

## COVERAGE

**COVERAGE** Johnstone's Trade Jonmat will cover up to 16 square metres per litre depending on the nature and porosity of the surface being painted.



## FILM THICKNESS

Wet: 90µm, dry: 21µm.

## DRYING TIME

**RECOAT** Touch dry in 1-2 hours.  
Recoat after 2-4 hours.



## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

## THINNER

Thinner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010) This product contains max 3g/l VOC



## KEY PROPERTIES

- Improved application
- Perfect for new plaster
- Outstanding dry & wet opacity

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray (see below). If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or in damp conditions.

## SPRAY & THINNING APPLICATION

Thinning: sealing new or bare surfaces: up to 1.5 part clean water to 10 parts paint. Spray @ 2500 PSI / 172 bar with a 517 tip.

## AIRLESS SPRAY

Un-thinned: Spray @ 3000 PSI / 207 bar with 517 tip.  
Thinned: 1 part clean water to 10 parts paint spray @ 2500 PSI / 172 bar with 517 tip.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

5 Litre, 10 Litre, 15 Litre.