

DESCRIPTION

Johnstone's Trade Dry Lining Paint is a high quality flat matt emulsion, developed especially for use on bare dry lining boards. Its excellent opacity, coverage and application make it ideal for new work projects with critical lighting conditions.

RECOMMENDED USES

INTERIOR

Ceiling & walls.



TYPE OF SUBSTRATE

Suitable for use on plasterboard/wallboards/dry lining boards.

COLOUR RANGE

Available in Brilliant White only.

FINISH

Matt

VOLUME SOLID

27%

COVERAGE

COVERAGE

12-14
M²/LITRE

Johnstone's Trade Dry Lining Paint will cover approximately 12-14 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 90µm Dry: 24µm

DRYING TIME

RECOAT

2-4
HRS

Touch dry in 1-2 hours. Recoatable after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a):
30g/l (2010) This product contains
max 5g/l VOC



KEY PROPERTIES

- Wipeable dead matt emulsion
- Excellent opacity
- Ideal for use on dry lining boards.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Wear a suitable mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Johnstone's Trade Dry Lining Paint thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or in damp conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

10 Litre.