



Ultra Primer & Finish

DESCRIPTION

Johnstone's Trade Ultra Primer & Finish is a high performance, quick drying, alkali resisting primer and finish that is manufactured from high quality pigments and tough acrylic resin with enhanced stain blocking properties. It primes and seals porous surfaces as well as offering great adhesion to difficult to apply surfaces including galvanised metal, to provide a fast drying, low odour, sprayable durable finish.

Ideal for use in private, public and commercial buildings where its low odour properties, combined with ease of application and speed of drying, allow the work to be completed with a minimum of disruption.

RECOMMENDED USES



Suitable for interior use.

SPECIAL PROPERTIES

Rapid drying. Can be used over multiple substrates and hard to adhere to including galvanised metal.

COLOUR RANGE

Brilliant White.

FINISH

Eggshell.

VOLUME SOLID

45%.

COVERAGE



Johnstone's Trade Ultra Primer & Finish will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 45µm.

DRYING TIME



Touch dry in 30 minutes. Recoatable after 3 hours.

TRANSPORTATION & STORAGE

PROTECT FROM FROST. To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food.

THINNER

Thinner: Clean water

VOC CONTENT

EU limit value for this product (Cat A/g): 30g/l (2010). This product contains max 10g/l VOC.



KEY PROPERTIES

- Primer and Finish Coat in One
- Suitable Over Multiple Substrates
- Excellent Adhesion over Difficult Surfaces

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Surfaces should be suitably prepared before application. Rub down previously painted surfaces with fine waterproof abrasive paper. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. Apply one full coat, brushing firmly into the surface. Porous surfaces should be sealed with a first coat of Johnstone's Trade Ultra Primer & Finish thinned with up to 20% clean water. Allow 3 hours to dry under normal conditions before applying the required paint finish. Johnstone's Trade Ultra Primer & Finish can be applied by airless spray. Allow fresh plaster to dry thoroughly before application. Do not apply when air or surface temperature is below 10°C.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

10 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.