

## DESCRIPTION

Johnstone's Trade Quick Dry Matt Blackboard Paint gives an attractive smooth, non-reflective black finish formulated for interior use on wood and metal. Suitable for use on beams, panelling, doors, decorative ironwork, stage scenery, darkrooms and blackboards.

## RECOMMENDED USES



Beams, panelling, doors, decorative ironwork, stage scenery, darkrooms and blackboards.

## SPECIAL PROPERTIES

Non-reflective, washable.

## COLOUR RANGE

Black.

## FINISH

Matt.

## VOLUME SOLID

52%.

## COVERAGE



Johnstone's Trade Quick Dry Matt Blackboard Paint will cover approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 50µm, dry: 25µm.

## DRYING TIME



Touch dry in 1-2 hours. Recoatable after 2-4 hours.

## TRANSPORTATION & STORAGE

To avoid risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Cleaner: Clean Water

## VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010). This product contains max 15g/l VOC.



## KEY PROPERTIES

- Matt finish
- For interior wood and metal

## PREPARATION

All surfaces to be painted should be sound, clean, dry and free from loose and flaking material. Previously painted surfaces should be rubbed down with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime bare surfaces with the appropriate Johnstone's Trade Specialist Primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Ensure good ventilation during application and drying. Stir well before use and apply by brush or roller. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading. Under normal conditions the paint is touch dry in 1-2 hours. Allow 2-4 hours before applying a second coat if required. Do not apply when air or surface temperature is below 10°C or in damp conditions.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

1 Litre and 2.5 Litre.