

## DESCRIPTION

Johnstone's Trade Woodworks Knotting Solution is a quick drying solution suitable for preventing resinous sap bleeding through knots in wood and discolouring paint or varnish finishes. Conforms to BS1336.

## RECOMMENDED USES



Suitable for interior & exterior use.

## TYPES OF SUBSTRATE

Interior and exterior bare timber with knots, doors, door frames, furniture and railings.

## COVERAGE



Johnstone's Trade Woodworks Raw Linseed Oil will cover approximately 15 square metres per litre, depending on the nature and porosity of the timber.

## DRYING TIME



Recoat after 30 minutes under normal conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION.

## CLEANER

Cleaner: Methylated Spirits.

## VOC CONTENT

EU limit value for this product (Cat A/h): 750g/l (2010). This product contains max 750g/l VOC.



## KEY PROPERTIES

- Seals knots and sap streaks in wood
- Prevents topcoat discoloration
- Can be overcoated after 30 minutes

## PREPARATION

Ensure that the wood to be treated is thoroughly clean and dry and free from resinous matter or loose particles. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Rub down the surface with abrasive paper to provide a key. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure maximum ventilation during application and drying. Shake well before use. Using a brush or lint free cloth, apply a liberal coat and leave to dry. Apply a full coat with the minimum if brush work. Touch dry in 5-10 minutes. If a second coat is required, this can be applied after 30 minutes, but brushing must be kept to a minimum to avoid working-up the underlying film. Will cover approximately 10 square metres per litre.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with Methylated Spirits. Replace lid firmly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Application cloths and cleaning rags impregnated with product may spontaneously combust. Dispose of safely to avoid fire risks. Saturate all soiled cloths with water and place outside for disposal.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

250ml