



Two Pack Adhesion Promoting Primer

DESCRIPTION

Johnstone's Trade 2 Pack Adhesion Promoting Primer is a water based curing system which promotes adhesion on difficult substrates such as glazed tiles or as a barrier coat against previously painted surfaces. Acts as a barrier coat and promotes adhesion over previously painted surfaces, glazed tiles, matt tiles, quarry tiles, ferrous and nonferrous metals, cement render, blockwork, brickwork, masonry and even tarmac surfaces.

RECOMMENDED USES



Acts as a barrier coat and promotes adhesion over previously painted surfaces, glazed tiles, matt tiles, quarry tiles, ferrous and non-ferrous metals, cement render, blockwork, brickwork, masonry and even tarmac surfaces.

SPECIAL PROPERTIES

Superior adhesion and 'bleed' resistance.

COLOUR RANGE

White.

FINISH

Matt.

VOLUME SOLID

50%.

COVERAGE



Johnstone's Trade 2 Pack Adhesion Promoting Primer will cover at a rate of approximately 7-8 square metres per litre depending on the nature and porosity of the surface.

FILM THICKNESS

Wet: 75µm, dry: 35µm.

DRYING TIME



Touch dry in 4 hours. Recoatable after 16 hours (minimum) and 7 days (maximum).

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Thinner: Water. Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/j): 140g/l (2010). This product contains max 80g/l VOC.



KEY PROPERTIES

- Coats difficult to paint surfaces
- Promotes adhesion of top coats

PREPARATION

INSTRUCTIONS: This is the base pack of a 2 pack product. the correct amount of activator is contained in the smaller tin and must be added and mixed thoroughly before use. the mixture must be used within 1.5 hours. partly used containers must not be resealed after use due to pressure build up.

All surfaces to be painted should be thoroughly degreased. Old gloss paint should be lightly abraded and degreased. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonetrade.com.

APPLICATION



The base and activator should be mixed together at a ratio of 2.5 / 0.5 by volume - ensure that the components are completely mixed together before application. Apply one coat by brush or roller. Apply the top coat within 24 hours of application of the primer. The mixture must be used within 1.5 hours of mixing.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Mixed, part used container must not be resealed after use, due to pressure build up. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonetrade.com or call 01924 354354

SIZE

2.5 Litre (2L Base + 0.5L Activator).



For more information on our products and services call 01924 354354 or visit www.johnstonetrade.com.