



Stormshield Water Seal

DESCRIPTION

Johnstone's Trade Stormshield Water Seal provides a water repellent surface on porous exterior, above ground masonry surfaces. It allows the substrate to breathe without changing its appearance. Johnstone's Trade Stormshield Water Seal will not remedy structural defects.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Clear.

FINISH

Transparent.

VOLUME SOLID

9%

COVERAGE



Johnstone's Trade Stormshield Water Seal will cover approximately 3-5 square metres per litre depending on the nature and porosity of the surface being coated.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

DRYING TIME



Touch dry in 4-6 hours. Recoatable after 8 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

Cleaner: White spirit.

VOC CONTENT

KEY PROPERTIES

- Creates a waterproof seal
- Allows surface to breathe
- Transparent appearance

PREPARATION

All surfaces to be coated should be clean, dry and free from loose and flaking material. Ensure all cracks etc are repaired. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure maximum ventilation during application and drying. Easy to apply by brush or roller. Apply a generous coat to provide maximum protection.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.