



WOODWORKS

Durable Quick Dry Polyurethane Varnish

DESCRIPTION

Johnstone's Trade Woodworks Durable Quick Dry Polyurethane Varnish is a specially formulated water based varnish for use on doors, windows, furniture and all interior smooth planed timber. It is non yellowing and provides a hardwearing, resistant finish which enhances the natural beauty of wood.

COLOUR RANGE

Clear Gloss and Clear Satin.

RECOMMENDED USES

Suitable for interior use.



TYPES OF SUBSTRATE

Quality timber, doors, window frames, furniture and all interior smooth planed timber.

COVERAGE

Johnstone's Trade Woodworks Durable Quick Dry Polyurethane Varnish will cover approximately 12 square metres per litre depending on the nature and porosity of the timber.



DRYING TIME

Touch dry in 1 hour. Recoatable after 2-4 hours. Conditions of high humidity will prolong drying time.



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/e): 130g/l (2010). This product contains max 80g/l VOC.



KEY PROPERTIES

- Superior durability
- Excellent abrasion and scratch resistance
- Non yellowing
- Reinforced with Polyurethane

PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Do not prepare the surface using steel wool. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir Johnstone's Trade Woodworks Durable Quick Dry Polyurethane Varnish thoroughly before use. Apply two or more coats of the varnish evenly, by brush along the grain, paying particular attention to the end grain. Do not overlap the brush strokes. On bare or new wood the first coat can be thinned with up to 10% clean water and followed by two coats of undiluted Johnstone's Trade Woodworks Durable Quick Dry Polyurethane Varnish. Sand down lightly between coats. Do not apply when temperatures are below 10°C. This product is not suitable for application over ferrous metal.

PLEASE NOTE: Johnstone's Trade Woodworks Durable Quick Dry Polyurethane Varnish is naturally milky in appearance when wet. This will disappear when completely dry. The final colour will depend on the original colour of the wood and the number of coats applied. It is advisable to test for colour in an inconspicuous area first.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

0.75 Litre and 2.5 Litre.



WOODWORKS

For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.