

## DESCRIPTION

Johnstone's Trade Stormshield Silicone Masonry paint is a high performance full silicone coating designed to provide excellent levels of water and weather resistance. Silicone technology provides high levels of breathability whilst repelling surface water to ensure long lasting protection for exterior surfaces. It is ideal for use directly over almost any previously painted, rendered or bare masonry surfaces and offers excellent levels of adhesion. The coating is also highly flexible to allow for surface movement to resist hairline cracking and water penetration. This product is ideal for use over surfaces that have previously been coated with silicone render or paint systems.

## RECOMMENDED USES



Ideal for use over masonry, renders, silicone based renders or cementitious surfaces that require a breathable coating.

## COLOUR RANGE

White and pastel colours.

## FINISH

Matt

## VOLUME SOLID

52%

## COVERAGE



Johnstone's Trade Stormshield Silicone Masonry Paint will cover approximately 7-8 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

wtf 130mic , dft 70mic

## DRYING TIME



Touch dry in 2 hours. Recoatable after 12 hours under normal, well ventilated conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST.

## Cleaner

Cleaner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/c): 40g/l (2010). This product contains max 5g/l VOC.



## KEY PROPERTIES

- High levels of water and weather resistance
- Silicone formulation maximises vapour transmission
- Flexible coating with excellent adhesion

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Fungicidal Wash as directed. Stabilise surfaces of a friable nature with Johnstone's Trade Stormshield Quick Dry Stabilising Solution as directed. When applying the first coat direct to new, untreated or porous surfaces, dilute the paint with approximately 5% clean water. Wear a suitable face mask when creating dust. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or textured roller. Also suitable for application by airless spray. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply when air or surface temperatures are below 8°C or when rain is imminent.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

5ltr