

DESCRIPTION

Johnstone's Trade Woodworks Satin Woodstain has been specially formulated for smooth timber joinery such as doors, windows, fascia boards, cladding and garden furniture, to provide a satin, microporous finish that highlights the natural grain of the wood. It is especially beneficial when used on exterior joinery (hardwood or softwood) but can also be used on interior wood and can be used as a maintenance coat over previously stained wood. Johnstone's Trade Woodworks Satin Woodstain has a BBA Approved 5 Year Guarantee when used as part of a system (see application). For maximum protection on new, bare and untreated wood first apply a suitable wood preserver.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak. A Range of colours available in 2.5 litre and 5 litre only via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPES OF SUBSTRATE

Doors, window frames, fascia boards, cladding, garden furniture.

COVERAGE



Johnstone's Trade Woodworks Satin Woodstain will cover at a rate of approximately 15 square metres per litre depending on the nature and porosity of the timber.

DRYING TIME



Recoat after 16 to 24 hours under normal conditions. Allow longer in adverse conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT AND FLAME.

CLEANER

White Spirit.

VOC CONTENT

EU Limit Value for this product (Cat A/e): 400 g/l (2010) This product contains max 400 g/l VOC



KEY PROPERTIES

- Excellent durability & weather protection
- Resists cracking, blistering & peeling
- Protects against harmful UV rays

PREPARATION

Ensure all surfaces to be stained are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any resins and natural oils using White Spirit. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Previously untreated softwood should be treated with a suitable clear preserver. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Stir Satin Woodstain thoroughly before use. Apply two or more coats of varnish evenly, by brush along the wood grain as required, paying particular attention to the end grain. On bare or new wood, apply at least two coats of Satin Woodstain to give maximum durability. A third coat may be required where extreme weather conditions exist. PLEASE NOTE: The final colour will depend on the original colour of the wood and the number of coats applied.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean application equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

750ml, 2.5 litre and 5 litre sizes.