

DESCRIPTION

Johnstone's Trade Damp Proof Paint is a white resin based paint specially formulated for application to damp interior wall surfaces. Can be left as a finish in its own right or as a damp proofing primer/sealer prior to over-painting with Johnstone's Anti-Mould Acrylic, or other Johnstone's decorative finish. It incorporates a water-reactive agent which takes care of residual surface moisture, but this does not remove the need to repair any structural faults which allow water to penetrate into the fabric of the wall.

Pliolite® is a registered trademark of Eliokem.

RECOMMENDED USES



Can be used over damp interior wall surfaces, either as a primer/sealer prior to overpainting or as a finish in its own right.

SPECIAL PROPERTIES

Incorporates a water-reactive agent which eliminates residual surface moisture.

COLOUR RANGE

White.

FINISH

Matt.

VOLUME SOLID

36%

COVERAGE



Johnstone's Damp Proof Paint will cover at the rate of approximately 4 square metres per litre. It is important to ensure that this total film thickness is achieved – do not overspread.

FILM THICKNESS

Wet: 250µm, dry: 90µm.

DRYING TIME



Recoat after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position.
STORE AWAY FROM HEAT AND FLAME.

THINNER

Cleaner: White Spirit

VOC CONTENT

EU limit value for this product (Cat A/I):
500 g/l (2010) This product contains
max 500 g/l VOC



KEY PROPERTIES

- For application to damp interior wall surfaces
- Damp proofing primer/sealer
- Contains Pliolite® resin

PREPARATION

This paint should be applied preferably to unpainted masonry surfaces. However, if these have been previously painted, remove as much of the old paint as possible by thorough scraping and wire brushing. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat any mould or lichen with Johnstone's Trade Sterilisation Wash before removing with a scraper or stiff brush, then treat surface again with Johnstone's Trade Sterilisation Wash. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. Stir well before use. A thick film is necessary for maximum effectiveness. Apply by brush or roller. Follow with subsequent Johnstone's Trade decorative finish, or leave as a finish in its own right.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre