

## DESCRIPTION

Johnstone's Trade New Build Professional Matt is a superior trade matt, specifically designed to meet the needs of New Build construction. With excellent high wet & dry opacity, delivering complete obliteration in 2 coats. With superior touch up properties and easy application, contractors can work with confidence to deliver clean and bright spaces with a professional finish.

## RECOMMENDED USES



Suitable for interior use.

## TYPE OF SUBSTRATE

Broad walls, New plaster, Taped dry lined board, Skimmed plaster board, Range of boards including anti condensation and acoustic.

## COLOUR RANGE

White & Magnolia, plus over 7,000 colours via the Johnstone's Tinting System.

## FINISH

Matt.

## VOLUME SOLID

32%.

## COVERAGE



Johnstone's Trade New Build Professional Matt will cover up to 16 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 62.5µm, dry: 20µm.

## DRYING TIME



Touch dry in 1-2 hours. Recoatable after 2-4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Thinner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 3g/l VOC.



## KEY PROPERTIES

- Superior Opacity
- Superior Touch up properties
- Designed for New Build construction
- Fast Drying

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray (see below). If more than one can of a colour is to be used in the same area, intermix before use. Ensure good ventilation during application and drying. Do not apply in temperatures below 10°C or in damp conditions.

## SPRAY & THINNING APPLICATION

**THINNING:** sealing new or bare surfaces: up to 1.5 part clean water to 10

parts paint. Spray @ 2500 PSI / 172 bar with a 517 tip.

**AIRLESS SPRAY:**

**UN-THINNED:** Spray @ 3000 PSI / 207 bar with 517 tip.

Thinned: 1 part clean water to 10 parts paint spray @ 2500 PSI / 172 bar with 517 tip.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

10 Litre.