

## DESCRIPTION

Johnstone's Trade Anti-Condensation Paint is a water based paint which provides a matt coating for interior surfaces. Reduces condensation by absorbing an amount of the condensed water and releasing it back into the atmosphere over time.

## RECOMMENDED USES



Can be used on most interior surfaces, after suitable preparation and priming, where intermittent water condensation is a problem.

## SPECIAL PROPERTIES

Reduces condensation by absorbing the condensed water and allowing it to be slowly released back into the atmosphere.

## COLOUR RANGE

Brilliant White.

## FINISH

Matt.

## VOLUME SOLID

24%.

## COVERAGE



Johnstone's Trade Anti-Condensation Paint will cover approximately 13 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 200µm, dry: 70µm.

## DRYING TIME



Touch dry in 1 hour. Recoatable after 2 hours.

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST

## THINNER

Cleaner: Clean Water.

## VOC CONTENT

EU Limit Value for this product (Cat A/a): 30g/l (2010) This product contains max 3g/l VOC



## KEY PROPERTIES

- Ideal for use in areas prone to high moisture
- Ideal for use on new plaster

## PREPARATION

All surfaces to be painted should be sound, clean, dry and free from grease. Remove all loose and defective paint. Flat down glossy areas with abrasive paper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat any mould or lichen with Johnstone's Trade Sterilisation Wash before removing with a scraper or stiff brush then treat surface again with Johnstone's Trade Sterilisation Wash. Prime all areas of damp plaster or brickwork with Johnstones Trade Damp Proof Paint. Prime bare metal areas with Johnstones Trade Universal Primer. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. Suitable for application by brush or conventional spray. Apply two full coats. Do not apply when air or surface temperature is below 10°C. Brush marks can be camouflaged by stippling. The application of a protective coat of Johnstone's Trade Anti-Mould Acrylic Matt Finish over the dry film of Johnstone's Trade Anti-Condensation Paint is recommended.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

5 Litre