

DESCRIPTION

Johnstone's Trade Stormshield Textured Masonry is a premium quality, acrylic resin based paint formulated for exterior use on cement rendering, rough cast, brick and concrete. It provides a fine sand textured finish that bridges hairline cracks and helps to disguise uneven surfaces. Good anti-carbonation properties.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Tintable to a range of colours available in Voice of Colour exterior colours.

FINISH

Textured.

VOLUME SOLID

40%

COVERAGE



Johnstone's Trade Stormshield Textured Masonry will cover approximately 6-8 square metres per litre depending on the nature and porosity of the surface being painted. In common with all wall paints, the spreading rate will be reduced on rough and absorbent surfaces such as pebbledash.

FILM THICKNESS

Wet: 143µm, dry: 57µm.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 4-6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/c): 40g/l (2010). This product contains max 10g/l VOC.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.

KEY PROPERTIES

- Durable & weather resisting
- Excellent colour retention
- OVER 15 YEARS LIFE EXPECTANCY

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Trade Sterilisation Wash as directed. Stabilise surfaces of a highly porous or friable nature with Johnstone's Trade Stabilising Solution as directed. Before applying Johnstone's Trade Stabilising Solution to the whole surface, first carry out a test application to a small area. If this dries to a glossy film, thin with one part of White Spirit to two parts of Johnstone's Trade Stabilising Solution and then test again in another small area. If a glossy film still results, try a blend of equal parts of White Spirit and Johnstone's Trade Stabilising Solution. Wear a suitable face mask when creating dust. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by adapted conventional spray. Do not thin, except for absorbent surfaces, when a small quantity of clean water may be added. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre.