

DESCRIPTION

We know that on large broad wall surfaces, paint finishes are often subject to criticism due to the visible overlaps which can be seen in critical lighting. Whatever your project, Johnstone's Trade Perfect Matt creates a flawless finish with ease even on the most challenging projects. No longer worry about the impact of visible application marks highlighted by critical lighting or the cost of extra time on site due to spot repair. Johnstone's Trade innovative Smooth Layer technology allows you to complete projects stress free in any colour.

RECOMMENDED USES



Internal finish for all types of Interior walls and ceilings both bare and previously painted including plaster, plasterboard, concrete, ceiling tiles, wallcoverings etc. Ideal where the surface and site conditions, with critical lighting could combine to be a potential issue.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's tinting system.


FINISH

Flat Matt Finish.

VOLUME SOLID

37%

COVERAGE



Johnstone's Trade Perfect Matt will cover approximately up to 13 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet 100 microns and Dry 37 microns

DRYING TIME



Touch Dry in 1-2 hours.
Recoat after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a):
30g/l (2010) This product contains
max 10g/l VOC



KEY PROPERTIES

- Eliminates visible applications marks
- Flawless, flat matt finish
- Effortless spot repair

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade primer. Rub down previously glossed painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation or pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade Datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Do not breathe spray. Wear respiratory protection. Seal absorbent surfaces with a coat of Johnstone's Trade Perfect Matt thinned up to 5-10% with clean water. If more than one of a colour is to be used in the same area intermix before use. Do not apply in temperatures below 8°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings Do not empty product into drains or watercourses Do not use empty container for storing food (10L ONLY).

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

2.5, 5 and 10 litre