

DESCRIPTION

Johnstone's Trade Woodworks Heavy Duty Yacht Varnish has been specially formulated for use on all exterior smooth planed timber, doors and window frames. It provides a flexible varnish film that flexes with the timber surface whilst protecting the wood. To ensure maximum protection on new, bare and untreated wood first apply a suitable all purpose wood preserver.

COLOUR RANGE

Clear Gloss.

RECOMMENDED USES

Suitable for exterior use.



TYPES OF SUBSTRATE

Doors, window frames and all smooth planed exterior timber.

COVERAGE

Johnstone's Trade Woodworks Heavy Duty Yacht Varnish will cover approximately 15 square metres per litre depending on the nature and porosity of the timber.



DRYING TIME

Recoat after 16-24 hours under normal conditions. Sand down lightly between coats..



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.
STORE AWAY FROM HEAT AND FLAME.

CLEANER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.



KEY PROPERTIES

- Water repellent
- All weather UV protection
- Flexible coating
- Protects against cracking and peeling

PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Previously varnished surfaces in sound condition should be rubbed down with fine waterproof abrasive paper and rinsed thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For best results, new or bare wood should be lightly rubbed down along the grain with fine abrasive paper, any knots sealed with a clear knotting solution, treated with a suitable clear Wood Preservative and allowed to dry. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure maximum ventilation during application and drying. Stir Johnstones Trade Woodworks Heavy Duty Yacht Varnish thoroughly before use. Apply two or more coats of Johnstones Trade Woodworks Heavy Duty Yacht Varnish, evenly by good quality brush, along the wood grain, paying particular attention to the end grain. Do not overlap the brush strokes. On bare or new wood the first coat can be thinned with one part White Spirit to five parts Johnstones Trade Woodworks Heavy Duty Yacht Varnish and applied by brush followed by two coats of undiluted Johnstones Trade Woodworks Heavy Duty Yacht Varnish. Sand down lightly between coats.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

750ml, 2.5 litre and 5 litre sizes.