

### DESCRIPTION

Johnstone's Trade Woodworks Floor Varnish has been specially formulated for use on all interior timber floors from gymnasiums, dance floors and wooden stairs. It provides a tough, hardwearing protective finish that enhances the natural beauty of the wood. Ideal for "heavy traffic" areas and resists heat, chemical spillage and scratching.

### COLOUR RANGE

Clear Gloss and Clear Satin.

### RECOMMENDED USES

Suitable for interior use.



### TYPES OF SUBSTRATE

Interior timber floors and cork tiles.

### COVERAGE

Johnstone's Trade Woodworks Floor Varnish will cover approximately 17 square metres per litre depending on the nature and porosity of the timber.



### DRYING TIME

Recoat after 16-24 hours under normal conditions. Avoid heavy traffic until fully dried.



### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. STORE AWAY FROM HEAT AND FLAME.

### THINNER

Cleaner White Spirit.

### VOC CONTENT

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 400g/l VOC.



### KEY PROPERTIES

- Hardwearing, durable protective finish
- Ideal for heavy traffic areas
- Resists staining, scratching and abrasion
- Stain, chemical and heat resisting

### PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or crazed varnish. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

### APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. Stir Floor Varnish thoroughly before use. Apply two coats of varnish using a good quality brush, along the wood grain, as required. Do not overlap the brush strokes. Apply 2 or 3 coats as required, sand down lightly between coats.

### CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

### SIZES

2.5 litre and 5 litre sizes.