

DESCRIPTION

Johnstone's Trade Professional Gloss is a solvent based high sheen finish, which can be used for interior and exterior wood and metals. Johnstone's Trade Professional Gloss is a tough, durable product, which provides a high gloss finish that stays whiter for longer and offers outstanding application and coverage. For best results, use Johnstone's Trade Professional Undercoat.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

High gloss.

VOLUME SOLID

61%

COVERAGE



Johnstone's Trade Professional Gloss will cover approximately 17 square metres per litre, depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 60µm, dry: 37µm.

DRYING TIME



Recoat after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

STORE AWAY FROM HEAT AND FLAME. Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position.

CLEANER

Cleaner: White spirit.

VOC CONTENT

EU limit value for this product (Cat A/d): 300 g/l (2010) This product contains max 300 g/l VOC



KEY PROPERTIES

- Tough and durable solvent based gloss
- Outstanding application and coverage
- Provides a high gloss sheen finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a precoat of Johnstone's Trade Professional Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces. If more than one can of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

500ml, 1 Litre, 2.5 Litre, 5 Litre.