

DESCRIPTION

Johnstone's Trade Woodworks Teak Oil penetrates timber, replacing the lost natural oils and enhances the natural beauty of the wood. With a low sheen finish, it is ideal for the upkeep of exterior hardwood.

RECOMMENDED USES



Suitable for interior & exterior use.

TYPES OF SUBSTRATE

Interior and exterior bare timber with knots, doors, door frames, furniture and railings.

COVERAGE



Johnstone's Trade Woodworks Teak Oil will cover approximately 15-20 square metres per litre, depending on the nature and porosity of the timber.

DRYING TIME



Product will be recoatable after 12 hours at room temperature.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT AND FLAME.

CLEANER

White spirit.

KEY PROPERTIES

- Revives dull and dry timber
- Enhances the natural beauty of wood

PREPARATION

Ensure that the wood to be treated is thoroughly clean, dry, and free from resinous matter or loose particles. Clean oily timber with White Spirit. Rub down the surface with abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Apply Johnstone's Trade Woodworks Teak Oil liberally by using a cloth or brush. Remove excess Johnstone's Trade Woodworks Teak Oil after 10-15 minutes with a clean cloth. Up to 3 coats may be required for bare timber, rubbing previous coat with fine sandpaper for a key; use 1 coat for maintenance of existing coating.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine substitute. Replace lid firmly. Clean brushes immediately after use in White Spirit or Turpentine substitute. Application cloths and cleaning rags impregnated with product may spontaneously combust. Dispose of safely to avoid fire risks. Saturate all soiled cloths with water and place outside for disposal. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

500ml