

## DESCRIPTION

Johnstone's Trade Professional Undercoat is a solvent based undercoat, which can be used for interior and exterior wood and metals. Johnstone's Trade Professional Undercoat offers excellent adhesion and a high film build, which makes it suitable for sanding and hiding surface imperfections. It provides the perfect base for finishing Johnstone's Trade Professional Gloss, Satin Finish or Eggshell.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Wood and metal.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Not Applicable

## VOLUME SOLID

63%

## COVERAGE



Johnstone's Trade Professional Undercoat will cover approximately 16-18 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 60µm, dry: 38µm.

## DRYING TIME



Recoat after 16-24 hours under normal conditions.

## TRANSPORTATION & STORAGE

STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

## CLEANER

Cleaner: White spirit.

## VOC CONTENT

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.



## KEY PROPERTIES

- Superb application, coverage & opacity
- Excellent adhesion and high film build
- Perfect base for gloss finishing

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

500ml, 1 Litre, 2.5 Litre, 5 Litre.