

DESCRIPTION

Johnstone's Trade Aluminium Wood Primer is a solvent-borne blend of fine grade aluminium and high quality resin. Formulated for interior and exterior use on new or bare timber it provides a barrier against the oily exudations of naturally resinous timber, can be used as a sealer on scorched or smoke damaged surfaces, and is also self-knotting.

RECOMMENDED USES



For use on new or bare timber. Seals weathered creosote or smoke damaged surfaces. Primes resinous, scorched and smoke damaged timber and is also self knotting.

SPECIAL PROPERTIES

Can be used as a sealer on weathered creosote or smoke damaged surfaces.

COLOUR RANGE

Metallic Grey.

FINISH

Matt.

VOLUME SOLID

37%

COVERAGE



Johnstone's Trade Aluminium Wood Primer will cover approximately 13-15 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 75µm, dry: 28µm.

DRYING TIME



Recoat after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/g): 350g/l (2010). This product contains max 350g/lVOC



KEY PROPERTIES

- For use on new or bare timber
- Seals weathered concrete & smoke damaged surfaces

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Wash down oily timbers such as teak with White Spirit and allow to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well before use. Easy to apply by brush paying particular attention to the end grain.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

1 Litre, 2.5 Litre and 5 Litre.