

DESCRIPTION

Johnstone's Trade Woodworks Polyurethane Varnish is a traditional quality, tough and durable varnish for interior use on bare or previously treated, varnished timber. Suitable for use on doors, windows, furniture and all interior smooth planed timber giving tough protection.

COLOUR RANGE

Clear Gloss and Clear Satin.
A selection of colours available in 750ml Gloss only.

RECOMMENDED USES

Suitable for interior use.



TYPES OF SUBSTRATE

Doors, window frames, furniture and interior quality timber.

COVERAGE

Johnstone's Trade Woodworks Polyurethane Varnish will cover approximately 17 square metres per litre, depending on the nature and porosity of the timber.



DRYING TIME

Recoat after 16-24 hours under normal conditions.



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.
STORE AWAY FROM HEAT AND FLAME.

CLEANER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.



KEY PROPERTIES

- Tough and durable finish.
- Resistant to mild, household chemicals
- Traditional varnish for smooth planed timber
- Good abrasion resistance

PREPARATION

Ensure the timber to be varnished are sound, clean, dry and free from dust, grease, polish and any other surface contaminant. Remove any flaking or crazed varnish. Sound existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. Stir well before use. Apply Johnstone's Trade Woodworks Polyurethane Varnish evenly by brush along the wood grain using two or more coats as required. Sand down lightly between coats.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

750ml, 2.5 litre and 5 litre sizes.