

DESCRIPTION

Johnstone's Trade Woodworks Opaque Wood Finish is a premium quality, low maintenance, alkyd resin based wood coating for exterior use. It provides a mid sheen, opaque, microporous coating designed to protect from water, reduce blistering, cracking and peeling, and resist UV attack. Suitable for use on rough sawn exterior timber surfaces such as fences, gates and cladding. To ensure maximum protection on new, bare and untreated wood first apply a suitable wood preserver.

COLOUR RANGE

Burnt Walnut; Ebony; Forest Green; Jacobean Oak; Russet; Rustic Oak; White

A Range of colours available in 2.5 litre and 5 litre only via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES

Suitable for exterior use.



TYPES OF SUBSTRATE

Garden furniture, trellis work, cladding, sheds, gates, fascias, fencing, rough sawn and smooth planed timber.

COVERAGE

Johnstone's Trade Woodworks Opaque Wood Finish will cover approximately 12 square metres per litre, depending on the nature and porosity of the surface.



DRYING TIME

Recoat after 16–24 hours under normal drying conditions.



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT AND FLAME.

CLEANER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.



KEY PROPERTIES

- Covers surface imperfections
- Water repellent microporous formulation
- Low maintenance cycle
- Protects against damaging UV rays

PREPARATION

All surfaces to be treated should be clean, dry and free from loose or flaking material. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat any mould or lichen with sterilisation wash as directed. For maximum performance, old paint or varnish should be completely removed. Treat new or bare surfaces with a suitable clear preservative. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Do not stir. The brush should be fully loaded for best results. Apply paint evenly by brush and avoid overspreading. Recoatable after 16-24 hours under normal conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

2.5 litre and 5 litre sizes.