



Advanced Stain Block Primer

DESCRIPTION

Johnstone's Trade Advanced Stain Block Primer is a shellac based, heavy duty stain blocker. It is ideal for sealing tar, bitumen and creosoted surfaces to prevent bleeding through in subsequently applied solvent based paints. Seals stains in timber, wood composites, plaster, cement and brickwork as well as locking in unwanted odours.

RECOMMENDED USES



Primer and sealer for timber, wood composites, plaster, cement and brickwork. Seals tar, bitumen, creosoted areas.

SPECIAL PROPERTIES

Heavy stain blocking. Rapid drying. Can also be used as a quick drying white line paint.

COLOUR RANGE

Brilliant White.

FINISH

Matt.

VOLUME SOLID

45%.

COVERAGE



Johnstone's Advanced Stain Block Primer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 25µm.

DRYING TIME



Touch dry in 10 minutes.
Recoat after 30 minutes.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Cleaner: Mineralised Methylated Spirit.

VOC CONTENT

EU limit value for this product (Cat A/I): 500g/l (2010). This product contains max 500g/lVOC



KEY PROPERTIES

- Quick drying - recoat in 30 mins
- Locks in stains and odours
- Heavy duty stain blocker
- Interior, exterior spot primer
- Seals tar, bitumen & creosoted surfaces
- Benefits - Heavy stain blocking, Shellac based
Ideal on - Odour Sealing, Pencil, Tannin Bleed, Graffiti, Knots & Sap, Rust Staining, Smoke Damage/Odours, Water Damage/Stains, Nicotine/Tobacco, Mildew Stains, Pet Stains/Odours, Fire Damage/Odours, And more ...

PREPARATION

All surfaces to be painted should be clean, dry and free from oil, grease or loose and flaking material. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre 1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Stir well before use. Suitable for application by brush or roller. Apply a full coat, freely and smoothly with the minimum of brushwork. If a second coat is required, allow approximately 30 minutes before applying. Avoid over brushing.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with Mineralised Methylated Spirit. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.