

DESCRIPTION

Johnstone's Trade Woodworks Danish Oil is a blend of premium quality oils. The low viscosity allows deep penetration, nourishing the wood. With its water resistant qualities Johnstone's Trade Woodworks Danish Oil is suitable for interior and exterior application e.g. terraces, decking, furniture, timber cladding and structural beams.

RECOMMENDED USES

Suitable for interior and exterior use.



TYPE OF SUBSTRATE

Ideal for interior and exterior wood and timbers.

COLOUR RANGE

Clear.

FINISH

Satin.

VOLUME SOLID

35%

COVERAGE

First layer 13-20m² /l
Second layer 20-30m² /l
This is dependent on wood type.



FILM THICKNESS

Wet: 76µm; Dry 27µm.

DRYING TIME

Recoatable in 20 minutes. Recommended application and drying temperature is between 5-25°C. Low temperature and high humidity extend drying time of individual layers. Resinous wood also takes longer to dry on application. Wood moisture content should not exceed 20%.



TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

Cleaner: White Spirit

VOC CONTENT

EU limit value for this product (Cat A/f): 700g/l (2010). This product contains max 500g/l VOC.



KEY PROPERTIES

- Contains Tung Oil
- Deeply Nourishes and Protects
- Retains the natural colour of the wood

PREPARATION

Before applying Johnstone's Trade Woodworks Danish Oil ensure that all timber to be treated is sound, dry and free from dust, grease or any other surface contaminants. Treat any mould or lichen with a fungicidal wash as directed and protect exterior wood with Johnstone's Trade All Purpose Preserver. Use White Spirit to remove any natural oils or resins and allow to dry. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Stir Johnstone's Trade Woodworks Danish Oil thoroughly before use. Apply with brush. After 20 minutes remove any excess oil with a lint free cloth following the natural woodgrain. The surface should be uniform smooth and show no oily stains. When dry apply second coat. To ensure the aesthetic appearance and protection of the wood, maintain the substrate at least once a year. For best results maintain the wood twice a year i.e. in the Spring and in Autumn to prepare the wood for Winter.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Application cloths and cleaning rags impregnated with product may spontaneously combust. Dispose of safely to avoid fire risks. Saturate all soiled cloths with water and place outside for disposal. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

0.75 Litre.