

DESCRIPTION

Johnstone's Trade Stormshield Smooth Masonry is rain resistant after 20 minutes* and suitable for application between 2°C and 35°C. It is extremely durable with 15 years life expectancy which offers excellent weather and dirt resistance, together with great colour retention and opacity. Suitable for outdoor use on cement rendering, rough cast, brick and concrete.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash etc.

COLOUR RANGE

Tintable to a range of colours available in Voice of Colour exterior colours.

FINISH

Matt.

VOLUME SOLID

30%

COVERAGE



Johnstone's Trade Stormshield Smooth Masonry will cover up to 17 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 30µm.

DRYING TIME



Touch dry in 1 hour
Rain resistant after 20 minutes*
Recoat after 2-4 hours
*at 23°C and 50% humidity.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/c): 40g/l (2010). This product contains max 3g/l VOC.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.

KEY PROPERTIES

- Rain resistant after 20 minutes*
- All season application
- 15+ years life expectancy
- Excellent colour retention & opacity
- Anti-Carbonation properties

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Treat any fungal, algal or lichen with Johnstone's Trade Sterilisation Wash as directed. Johnstone's Trade Stormshield Smooth Masonry can be applied directly over bare surfaces (thinned 5% with clean water) and previously painted surfaces, provided these are clean, sound and firm. Stabilise surfaces of a highly porous or friable nature with Johnstone's Trade Stormshield Quick Dry Stabilising Solution as directed. Remove any limewash or distemper completely. Avoid the inhalation of dust. Wear a suitable face mask if creating dust. Repair cracks and defective areas with a suitable exterior filler. For more information and free Johnstone's datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. If more than one container of colour is to be used in the same area, intermix before use. Apply two full coats, allowing 2-4 hours between coats under normal drying conditions. Do not apply in temperatures below 2°C or in damp conditions. Suitable for application by brush, roller, conventional and airless spray. If applying by spray: Do not breathe spray; Wear respiratory protection.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Do not empty product into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings. Replace lid firmly.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

2.5 Litre, 5 Litre, 10 Litre.