

DESCRIPTION

Johnstone's Trade Vinyl Soft Sheen is a mid sheen emulsion that withstands normal levels of humidity and can be wiped clean. Use on interior walls and ceilings as an attractive alternative to silk and matt finishes.

RECOMMENDED USES

INTERIOR
 Suitable for interior use.

TYPE OF SUBSTRATE

Plaster and embossed wall coverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork etc.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Mid sheen.

VOLUME SOLID

28%

COVERAGE

COVERAGE
 Johnstone's Trade Vinyl Soft Sheen will cover approximately 12-13 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 90µm, dry: 25µm.

DRYING TIME

RECOAT
 Touch dry in 1-2 hours.
Recoat after 3-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a):
30g/l (2010) This product contains
max 10g/l VOC



KEY PROPERTIES

- Good opacity & coverage
- Scuff resisting wipeable finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION

APPLICATION METHOD
 Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Johnstone's Trade Vinyl Soft Sheen thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING

CLEAN IN WATER
 Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

1 Litre, 2.5 Litre, 5 Litre, 10 Litre.