

DESCRIPTION

Johnstone's Trade Stain Block Primer is suitable to contain unsightly stains caused by nicotine, smoke, marker pen, wax crayon, graffiti, tannin and water. It provides a tough durable matt coating which prevents stains bleeding through from the substrate. Johnstone's Trade Stain Block Primer will not prevent stains caused by water damage unless the fault has been eradicated, and the substrate allowed to dry. Can be overcoated with water based emulsions.

© Plioway is a registered Trademark of the OMNOVA

RECOMMENDED USES



Primer for use on plaster, masonry and wood to cover unsightly stains.

SPECIAL PROPERTIES

Tough durable matt coating which prevents stains bleeding through from the substrate. One coat coverage. Can be used over water stains, grease, nicotine, rust, graffiti and ink.

COLOUR RANGE

White.

FINISH

Matt.

VOLUME SOLID

42%

COVERAGE



Johnstone's Trade Stain Block Primer will cover approximately 8 square metres per litre depending on the nature and porosity of the surface.

FILM THICKNESS

Wet: 125µm, dry: 53µm.

DRYING TIME



Under normal conditions, recoatable after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/g):
350 g/l (2010) This product contains
max 350 g/l VOC



KEY PROPERTIES

- Prevents the reappearance of stains
- Great over water based stains
- Benefits - Blocks water stains, Plioway® based
- Ideal on - Plywood, Brick & Concrete, Cedar & Redwood, Pressure Treated Wood, Odour Sealing, Lipstick/Crayon, Tannin Bleed, Graffiti, Water Damage/Stains, Nicotine/Tobacco, Mildew Stains, Pet Stains, And more ...

PREPARATION

All surfaces should be clean, dry and free from grease. Remove any crazed or flaking paint. Rub down with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre 1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. Stir thoroughly before use and apply by brush or roller, covering the stain and a surrounding area of 20cm to ensure maximum containment. Heavily soiled areas may require additional coats.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Brush Cleaner. Replace lid firmly after use. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

1 Litre and 5 Litre.