

### DESCRIPTION

Johnstone's Trade Woodworks Decking Stain provides 3 years all weather protection for new and previously stained decking and cladding. The wax enriched formulation gives a one-step water repellent finish that is quick drying, long lasting and helps resist cracking, peeling and fading. Johnstone's Trade Woodworks Decking Stain adds a coat of colour and dries to give a tough matt finish. For maximum protection on new, bare and untreated wood first apply a suitable wood preserver.

### COLOUR RANGE

Rich Teak, Spanish Cedar, Natural Oak, Chestnut Brown.

### RECOMMENDED USES



Suitable for exterior use.

### TYPE OF SUBSTRATE

Decking and cladding.

### COVERAGE



Under normal conditions Johnstone's Trade Woodworks Decking Stain will cover approximately 12 square metres per litre.

### DRYING TIME



Under normal conditions touch dry in 1-2 hours and recoat after 4 hours. Allow longer in adverse conditions. Do not apply in temperatures below 10°C, in damp conditions or if rain is imminent.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

### CLEANER

Cleaner: Clean water.

### VOC CONTENT

EU limit value for this product (cat A/e): 130g/l (2010). This product contains max 10g/l VOC.



### KEY PROPERTIES

- 3 year all weather protection
- Protects against damaging UV rays
- Wax enriched for excellent water repellency
- Long lasting colour retention

### PREPARATION

Ensure the surface to be stained is clean, dry and free from dust, grease, polish or any other coatings such as paint or varnish. Nail and screw heads in joinery should be set below the surface and concealed by a suitable wood filler. New untreated soft wood should first be treated with a suitable wood preserver. For previously painted or varnished wood remove all traces of previous coatings before staining. Use a Paint & Varnish Stripper to remove traces of previous treatment then treat as for bare or new wood. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

### APPLICATION



Ensure good ventilation during application and drying. Stir well before use. Apply evenly with the use of a brush or pad working well into the timber and along the grain. Apply two coats to bare and previously preservative treated timber. Redecoration requires one coat.

### CLEANING



Remove as much product as possible from the application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly after use. Do not empty products into drains or watercourses. Some local authorities' have special facilities for the disposal of waste coatings.

### PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

### SIZES

2.5 Litre.