

Thermory source sustainable, high-quality timbers which are thermally-modified for durability, stability and rot-resistance. The timber will fade to grey naturally over time.



At Installation

6 Months +

1 Year +



Ageing scale depending on maintenance & exposure



FORM



Stock Item - Contact us for board length availability

- ▶ Thermo-treated Scots Pine (Pinus Sylvestris)
- ▶ Domed profile for water run-off
- ▶ 2-5 knots / lm
- ▶ Pre-grooved for compatibility with the Grad 'hidden-fix' system
- ▶ FSC Certified Product available
- ▶ Joist centres for domestic use: **50cm max**
- ▶ Standard gap between boards: 6mm
- ▶ Compatible Grad rails:
 - PR 24 (120)
 - PR 39 (120)
 - PR 56 (120)
 - Flat Rail (120)

STRONG



- ▶ Soft wood, low density of 410kg/m³
- ▶ Maximum dimensional variations of 3%
- ▶ Class 3 Timber
- ▶ DTU 51.4: 100Kg minimum pull-out at 2 attachment points, certified by Critti Bois Test Centre

DURABLE



- ▶ Does not require additional treatment other than regular cleaning
- ▶ The original wood colour can be retained with regular oil treatment
- ▶ 15 Year Warranty – conditions of warranty upon manufacturer's guidelines and quality criteria available from info@outdoordeck.co.uk



Europe
Certified Wood



Clean
Every 6 months



15 Years

15 Years
According To Warranty
Conditions

QUALITY IN A CLICK >