

Technical information *такмас wR440 SAND*

Product Information

Location: Manchester road, Congleton, Cheshire. CW12 2LU

Туріса	XRF chemical analysis%					
Particle density				Iron oxide	as Fe_2O_3	0.32
Oven dried	2.55	Mg/m ³		Calcium oxide	as CaO	0.42
Saturated surface dried Apparent Water Absorption	2.57 2.58 0.1	Mg/m ³ Mg/m ³ %	BS EN 1097-6: 2000 (clause 9)	Silicon oxide	as SiO ₂	96.14
Water soluble Chloride	< 0.001	%	BS EN 1744-1: 2009 (clause 7)	Magnesium oxide	as MgO	0.12
Total Sulfur (as S)	<0.1	%	BS EN 1744-1: 2009 (clause 11)	Aluminium oxide	as Al_2O_3	1.30
Acid soluble Sulfate	<0.1	%	BS EN 1744-1: 2009 (clause 12)	Phosphorus oxide	as P_2O_5	0.05
Water soluble Sulfate (as SO ₃)	0.01	%	BS EN 1744-1: 2009 (clause 10)	Manganese oxide	as MnO	0.02
Bulk density (loose)	1.54	Mg/m³	BS EN 1097-3: 1998	Sulphur oxide	as SO₃	<0.01
Calcium carbonate equivalent	1.00	%	BS EN 196-21: 1992	Titanium oxide	as TiO ₂	0.04
рН	9.1		BS 1377-3: 1990 (clause 9)	Potassium oxide	as K2O	0.63
Drying Shrinkage	0.019	%	BS EN 1367-4: 2008	Sodium oxide	as Na2O	<0.08
Lightweight contaminators	<0.1	%	BS EN 1744-1: 2009 (clause 14)	Loss on ignition	@ 1000°C	0.7

Sieve size	Passing%	Additional information	
2mm	100	Petrological description: Quartzose Sand Particle shape: Angular to well rounded Surface texture: Rough to smooth	
- 1mm	99.9		
0.5mm	97.0		
0.250mm	31.0		
0.125mm	0.3		
0.063mm	0		

Notes

- 1. The above data is provided in good faith as a guide to
- typical values and does not constitute a specification. 2
- The company reserves the right to revise the data at any time. Individual certification available on request. 3.

The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.

For more details contact:

03456 007 703

www.tarmac.com

Tarmac Building Products Ltd Tunstead House, Buxton, SK17 8TG