


## **Key Features**

- Excellent sound attenuation (39 dB sound reduction) to eliminate the need for sound barriers in close office applications
- Enhanced acoustical absorption performance of 0.60 Q<sub>w</sub> for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- // Improved aesthetics with discreet perforations, a smoother finish and a classleading, fully painted whiteness
- Easy to handle and re-engineered for a better, easier fit
- Ideal for individual offices and board rooms



Edge Detail	Board	Tegular24	Tegular15
	124	0 24	
Thickness (mm)	19	19	19
Modules (mm)	600 x 600 5477M	600 x 600 5479M	600 x 600 5481M
Suspension Systems	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty²	Gridline 24 Butt Cut / Joggled Prelude 24 Sixty²	Gridline 15 Butt Cut Interlude HRC Silhouette
Colour	Global White		
Sustainability			eurofins
	37	A+ EN 13964 / E1	IFIED PROV
Acoustics	<b>*</b>		



 Qw
 Dnfw
 Rw
 Class
 NRC
 125
 250
 500
 1000
 2000
 4000

 Board, Tegular24, Tegular15
 0.60
 39 dB
 20 dB
 C
 0.55
 0.35
 0.40
 0.60
 0.65
 0.75
 0.65

**Fire Reaction** 



Euroclass A2-s1, d0 EN 13501-1

Performances & Features



85%



95% RH







Hz  $\alpha_P$ 





7.9 Kg/m²







If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

TDS 135.2.03.24

